



## Kendrick Dew Controllers Model Comparison

Model	Channels	Maximum Current (amps)		DC Power Accessory Ports	8V DSLR Power	Low Voltage Warning	Low Voltage Cut-Off	Disable Low Voltage Cut-Off	Lights Auto-Dim	Graphic Display	Temperature Sensing	Ambient Temperature Sensing	RFI Clean
		Heater Channels	Combined MAX Current										
Standard Dual Channel	2	4.1	7 †	NO	NO	YES	YES	NO	NO	NO	NO	NO	YES
Dewminator 4-Channel	4	4.1	7/15 † ‡	2 each - 12VDC	NO	YES	YES	YES	YES	NO	NO	NO	YES
DifiFire FX-PRO 4-Channel	4	4.1	7/15 † ‡	2 each - 12VDC	YES- programmable 8V or 12V	YES	YES	YES	YES	Yes - OLED	YES-Ports 1&2	YES	YES

†Cigarette Plugs & Barrel Connectors are limited to 7 Amps

‡Max Combined Current (amps) can be increased by exchanging the Cigarette Plug with Anderson Connectors

*Beware of competitors that claim high current (amps) capabilities. Despite manufacture claims, the current capacity of connectors (plugs) and power cord wire gauge are governed by the laws of physics.*