Lithium Power Pack Model Comparrison

| Specs | Standard Lead-Acid | | New LifePo4 |
|--------------------------------|---|---|---|
| Rated Capacity (Amp- Hours) | 18 | 33 | 50 |
| USEABLE Amp-Hour | 9 | 16.5 | 50 |
| Chemistry | Sealed Led-Acid | Sealed Led-Acid | LifePo4 (Lithium Iron Phosphate |
| Dimensions: | 8.25" L x 3.5" W x 9.25" H 21cm X 8.8cm X 23.5cm | 8.25"L x 5.5" W x 9.25" H (21cm X 14cm X 23.5cm) | 8.25"L x 5.5" W x 9.25" H (21cm X 14cm X 23.5cm) |
| Weight | 14 lb (6.4 kg) | 39 lb (19.5 kg) | 15.4 lb (7.0 kg) |
| USB Charging Ports? | NO | NO | YES |
| Battery Meter | Voltage Only | Voltage Only | Shunt Based: Current/Voltage/Power Remaining |
| Service Life (Cycles) | 200-500 | 200-500 | 4000-6000 |
| Smart Charger Included | 0.75 Amp | 1.25 Amp | 10 Amp |
| Option Inverter | Yes: 15V/18V/24V | Yes: 15V/18V/24V/48V | Yes: 15V/18V/24V/48V |
| Special Features | N/A | N/A | *BMS (Battery Management System) with Overcurrent and High-Low Current and Temperature Protection |
| Padded Carry Bag with | | | |
| Strap | Yes. Included | Yes. Included | Yes. Included |

^{*}BMS will also prevent charging when battery internal temperature is below 0C (32F)